



TRADEMARK HARDWARE

WORLD OF QUALITY HARDWARE

6000 Series

Grade 2 Medium Duty
Overhead Door Holder and Stop

Notes:

- Adjustable arms provide easy installation
- Slide track design
- Adjustable in the field
- Heavy shock absorber spring provides 5" to 7" compression before deadstop
- Special templating upon request



PRODUCT SPECIFICATIONS

CERTIFICATIONS:

- BHMA Certified ANSI A156.8
- UL/cUL Listed for up to 3 hours (stop only)
- UL10C Positive Pressure Rated (stop only)
- UL10B Neutral Pressure Rated (stop only)

WARRANTY:

- Five-year

MOUNTING STYLE:

- Concealed
- Surface

DOORS:

- Single acting doors for concealed and surface mounted
- Double acting doors for concealed mounted only

DOOR THICKNESS:

- 1-3/4" (44 mm) thick door - Standard
- 1-3/8" - 2-1/4" (36 mm - 57 mm) thick door - Optional

FUNCTIONS:

- 15- Friction
- 16- Stop Only
- 17- Hold Open

DOOR SIZES - DOOR WIDTH:

- Size 1 (SZ1) = 18"-33" (concealed mounted) 20"- 33" (surface mounted)
- Size 2 (SZ2) = 33"-51"

HANDING:

- Non-handed

OPENINGS:

- Degree of opening is fully adjustable and can be adapted to changing needs between 85°-110°

MATERIALS:

- Steel
- Stainless steel

FINISHES:

- US3, US10B
- US32D (for stainless steel)
- ALM

FASTENERS:

- Standard screw packet included for wood or metal door and frame applications



www.tmhardware.com



845-388-1300



845-388-1388



sales@tmhardware.com