

# 7000 Series

Grade 1 Heavy Duty Overhead Door Holder and Stop

#### Notes:

- Adjustable arms provide easy installation
- Slide track design
- Adjustable in the field
- Heavy shock absorber spring provides 5° to 7° compression before deadstop
- Special templating upon request



#### PRODUCT SPECIFICATIONS

#### CERTIFICATIONS:

- BHMA Certified ANSI A156.8
- UL/cUL Listed for up to 3 hours (stop only)
- UL10C Positive Pressure Rated (stop only)
- UL10B Neutral Pressure Rated (stop only)

# WARRANTY:

- Five-year

# MOUNTING STYLE:

- Concealed
- Surface

- Single acting doors for concealed and surface mounted
- Double acting doors for concealed mounted only

# DOOR THICKNESS:

- 1-3/4" (44 mm) thick door Standard 1-3/8" 2-1/4" (36 mm 57 mm) thick door Optional

#### FUNCTIONS:

- 15- Friction
- 16- Stop Only
- 17- Hold Open

# DOOR SIZES - DOOR WIDTH:

- Size 1 (SZ1) = 24"- 40"
- Size 2 (SZ2) = 41\*- 55\*

#### HANDING:

- Non-handed

#### OPENINGS:

- Degree of opening is fully adjustable and can be adapted to changing needs between  $85^{\circ}\text{-}110^{\circ}$ 

#### MATERIALS

- Steel
- Stainless steel

### FINISHES:

- US3, US10B, US26D (for steel)
- US32D (for stainless steel)
- ALM

# FASTENERS:

- Standard screw packet included for wood or metal door and frame applications







